



A-EFL13350 / A-EFL13375 ElectroStreak 1.1m BNF Basic (AS3X+ & SAFE) / PNP

Inspired by the original scratch-built design that was later sold in kit and ARF versions, the E-flite ElectroStreak 1.1m is designed to include numerous modern-day features and conveniences - along with excellent handling and high-speed performance! It assembles quickly and easily with just a few screws and is conveniently sized to be easy to store and transport without disassembly. It's also easier to launch and land than low-wing high-speed models like the V900, especially the BNF Basic version that's equipped with enhanced AS3X+ and optional-use SAFE Select technologies. And both versions include Spektrum digital, metal-g geared servos, a 45A Smart Lite ESC, plus a 3S and 4S compatible motor!



FEATURES

- Specially tuned motor compatible with 3S and 4S batteries without the need for modifications or upgrades
- Extremely wide flight envelope from unexpectedly stable slow-flight to locked-in precision aerobatic capabilities and beyond
- Factory-installed brushless outrunner motor plus APC 8x8E prop, and spinner with an aluminium backplate
- Receiver loaded with a Smart Transmitter File that allows you to import all settings for NX and iX series transmitters during the binding process
- The unmatched stability and locked-in feel of exclusive and enhanced AS3X+ technology
- Easier to launch than low-wing models especially with the automatic Hand Launch Assist Mode
- Fast and easy bolt-together assembly - no glue or special tools required
- Convenient top mounted hatch provides easy access to the battery
- Optional-use flaperons and spoilerons for added capabilities

IN THE BOX

- (1) E-flite ElectroStreak 1.1m with:
- (1) Spektrum BL Outrunner Motor
- (4) Spektrum Digital, MG Servos
- (1) Spektrum Avian 45-Amp Smart Lite Brushless ESC
- (1) Spektrum AR631+ 6-Channel Receiver (BNF Basic Only)
- (1) Product Manual

NEEDED TO COMPLETE

- BNF Basic**
- (1) Full-range 4-5+ channel Spektrum DSMX/DSM2 compatible transmitter
- PNP**
- (1) Full-range 4+ channel transmitter and receiver
- Both Versions**
- (1) 3S 11.1V or 4S 14.8V 1800-2200mAh LiPo with EC3 or IC3 Connector
 - (1) Compatible LiPo charger